

Vacuum units C-PAK 20-2500


3 x 208 V / 60 Hz 3 x 460 V / 60 Hz

3 x 230 V / 60 Hz 3 x 575 V / 60 Hz

3 x 400 V / 60 Hz

Technical Description

C-Pak 20-2500 Vacuum Unit

	Description	Part Number
	<p>C-PAK 20-2500 units</p> <p>Application: Welding extraction, on-torch or nozzles. Semi-portable installations.</p> <p>Capacity: Max. flow at rated motor power: 2353 cfm Max. vacuum: 88 in. W.G. Design: 1471 cfm at 80 in. W.G.</p> <p>Description: Vacuum unit with V-belt driven high pressure fan. Fan unit, filters / cyclone and starter are built into a heavy duty container. The unit has four Ø 160 mm / 16 in. vacuum inlets with connection flanges suitable for the PAK hose and coupler system. Flow restrictor and combined back flush/ start-up valve is standard.</p> <p>Noise level: 78 dB(A). At discharge air side: 85 dB(A).</p> <p>Dimensions: L x W x H: 2400 x 2100 x 2625 mm. 95 x 83 x 103 in.</p> <p>Weight: 1420 kg. / 3130 lb.</p>	<p>40 0512 30</p>
	<p>C-PAK 20-2500 C* Unit including FlexFilter cyclone for coarse separation. Voltage: 3 x 208 V 60 Hz. Power: 50 hp. Manual start / stop.</p>	<p>40 0512 40</p>
	<p>C-PAK 20-2500 C* Unit including FlexFilter cyclone for coarse separation. Voltage: 3 x 230 V 60 Hz. Power: 50 hp. Manual start / stop.</p>	<p>40 0512 50</p>
	<p>C-PAK 20-2500 C* Unit including FlexFilter cyclone for coarse separation. Voltage: 3 x 400 V 60 Hz. Power: 50 hp. Manual start / stop.</p>	<p>40 0512 60</p>
	<p>C-PAK 20-2500 C* Unit including FlexFilter cyclone for coarse separation. Voltage: 3 x 460 V 60 Hz. Power: 50 hp. Manual start / stop.</p>	<p>40 0512 70</p>

*NB. The C-PAK 20-2500 unit is equipped with FlexFilter cyclone (C-PAK).